Official

IN THE CLAIMS

Added claims:

143. (Added) A method, comprising the steps of:

forming a composition including a transition metal, a group IIIB element, an alkaline earth element, and oxygen, where said composition is a mixed transition metal oxide having a non-stoichiometric amount of oxygen therein and exhibiting a superconducting state at a temperature greater than 26°K,

maintaining said composition in said superconducting state at a temperature greater than 26°K, and

passing an electrical current through said composition while said composition is in said superconducting state.

144. (Added) The method of claim 143, where said transition metal is copper.

145. (Added) A superconductive method for causing electric current flow in a superconductive state at a temperature in excess of 26 K, comprising:

(a) providing a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the composition having a superconductor transition temperature T_c of greater than 26 K;

(b) maintaining the superconductor element at a temperature above 26 K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) causing an electric current to flow in the superconductor element.

146. (Added) The superconductive method according to claim 145 in which the copper-oxide compound of the superconductive composition includes at least one element selected from the group consisting of a rare-earth element and a Group III B element and at least one alkaline-earth element.

147. (Added) The superconductive method according to claim 146 in

which the rare-earth or rare-earth-like element is lanthanum.

148. (added) The superconductive method according to claim 146 in which the alkaline-earth element is barium.

149. (Added) The superconductive method according to claim 145 in which the copper-oxide compound of the superconductive composition includes mixed valent copper ions.

150. (Added) The superconductive method according to claim 149 in which the copper-oxide compound includes at least one element in a nonstoichiometric atomic proportion.

151. (Added) The superconductive method according to claim 150 in which oxygen is present in the copper-oxide compound in a nonstoichiometric atomic proportion.

152. (Added) A superconductive method for conducting an electric current essentially without resistive losses, comprising:

(a) providing a superconductor element made of a superconductive composition, the superconductive composition

consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the copper-oxide compound including at least one element selected from the group consisting of a rare-earth element and a Group III B element and at least one alkaline-earth element, the composition having a superconductive/resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{\rho=0}$, the transition-onset temperature T_c being greater than 26 K;

(b) maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{\rho=0}$ of the superconductive composition; and

(c) causing an electric current to flow in the superconductor element.

153. (Added) The superconductive method according to claim 152 in which said at least one element is lanthanum.

154. (Added) The superconductive method according to claim 152 in

which the alkaline-earth element is barium.

155. (Added) The superconductive method according to claim 152 in which the copper-oxide compound of the superconductive composition includes mixed valent copper ions.

156. (Added) The superconductive method according to claim 155 in which the copper-oxide compound includes at least one element in a nonstoichiometric atomic proportion.

157. (Added) The superconductive method according to claim 156 in which oxygen is present in the copper-oxide compound in a nonstoichiometric atomic proportion.

158. (Added) A superconductive method for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

(a) providing a superconductor element made of a superconductive composition, the superconductive

composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the composition having a superconductive transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element, a rare earth element; and a Group III B element;

(b) maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) causing an electric current to flow in the superconductor element.

159. (Added) A superconductive method for conducting an electric current essentially without resistive losses, comprising:

(a) providing a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the copper-oxide

compound including at least one element selected from the group consisting of a Group II A element, a rare earth element and a Group III B element, the composition having a superconductive/ resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{\rho=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{\rho=0}$ of the superconductive composition; and

(c) causing an electric current to flow in the superconductor element.

160. (Added) A superconductive method for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

(a) providing a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite

crystal structure, the composition having a superconductive transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element;

(b) maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) causing an electric current to flow in the superconductor element.

161. (Added) A superconductive method for conducting an electric current essentially without resistive losses, comprising:

(a) providing a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the copper-oxide compound including at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting

of a rare earth element and a Group III B element, the composition having a superconductive/resistive transition defining a superconductive-resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{\rho=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{\rho=0}$ of the superconductive composition; and

(c) causing an electric current to flow in the superconductor element.

162. (Added) A superconductive method for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

(a) providing a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a transition metal oxide compound having a substantially layered perovskite crystal structure, the composition having a superconductive

transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element;

(b) maintaining the superconductor element at a temperature above 26°K and below the superconductor transition T_c of the superconductive composition; and

(c) causing an electric current to flow in the superconductor element.

163. (Added) A superconductive method for conducting an electric current essentially without resistive losses, comprising:

(a) providing a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a transition metal-oxide compound having a substantially layered perovskite crystal structure, the transition metal-oxide compound including at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and